


GRADING NOTES:

1. PREPARE EROSION CONTROL PLAN AND OBTAIN GRADING PERMIT FROM MDNR.
2. INSTALL EROSION CONTROL DEVICES PRIOR TO DISTURBING SOIL.
3. GRADE AREAS SMOOTH AND FLOWING SURFACES THAT ATHLETES WILL BE ABLE TO RUN ON.
4. PROVIDE ADEQUATE SLOPE TO ALL SURFACES TO PROVIDE POSITIVE DRAINAGE.
5. APPLY EROSION CONTROL FABRIC (+/- 6 MOS.) OVER ALL SURFACES WITH A SLOPE GREATER THAN 5:1 (20%)
6. LOCATE ALL UTILITIES BEFORE CONSTRUCTION BEGINS.
7. NOTIFY OWNER REPRESENTATIVE OF ANY LAYOUT DISCREPANCIES.
8. AREAS INDICATED FOR SEEDING ARE DEPENDENT ON GRADING. ALL DISTURBED AREAS NOT DESIGNATED FOR OTHER PLANTING SHALL BE SEEDED, WITH A BLEND OF 80% TURF TYPE TALL FESCUE 10% BLUEGRASS AND 10% RYEGRASS.
9. THE LINES AND GRADES ARE INTENDED TO "FLATTEN" AREAS OF THE RUNNING COURSE. THE CONTRACTOR WILL PROVIDE THEIR OWN EARTHWORK CALCULATIONS. IF ADDITIONAL MATERIAL IS NEEDED, NOTIFY THE OWNER AND AN AREA ON SITE WILL BE IDENTIFIED TO USE. CONVERSLY, IF THERE IS AN EXCESS OF MATERIAL GENERATED FROM THE WORK, THE OWNER WILL IDENTIFY LOCATIONS ON SITE TO "LOSE" THE SOIL. ALL BORROW AND/OR FILL AREA SHALL BE SEEDED WHEN COMPLETE AND THE CONTRACTOR SHALL PROVIDE EROSION CONTROL MEASURES.



NORTH
1" = 100'



LEGEND

- = PROPERTY LINE
- ▲ = CONTROL POINT
- = ELECTRIC BOX
- ◇ = TELEPHONE PEDESTAL
- ↓ = GUY WIRE
- ⊕ = BENCHMARK
- ⊙ = FIRE HYDRANT
- ⊥ = SIGN
- ⊘ = POWER POLE
- = LIGHT POLE
- = TREE
- = MANHOLE
- ⊙ = WATER METER
- ▶ = WATER VALVE
- CMP = CORRUGATED METAL PIPE
- RCP = REINFORCED CONCRETE PIPE
- PVC = POLYVINYL CHLORIDE FLEX
- HDPE = CORRUGATED PLASTIC PIPE
- F/L = FLOW LINE
- W — = WATERLINE
- SS — = SANITARY SEWER LINE
- ST — = STORM SEWER LINE
- OE — = OVERHEAD ELECTRIC LINE
- UE — = UNDERGROUND ELECTRIC LINE
- FO — = FIBER OPTIC LINE
- = TREE LINE
- = CONCRETE
- ▨ = ASPHALT
- ▩ = GRAVEL/DIRT

+/-160 LF. 24" SOLID, HDPE N-12 PIPE. ANCHOR AT BOTTOM OF SLOPE AND INSTALL CMP FLARED END SECTION WITH 4' WIDE x 15' RIP RAP. UPPER END TO HAVE 36" RD. NYLOPLAST INLET WITH CAST IRON DOMED LID. PLACE 2' x 6" THICK, WIDE CONCRETE COLLAR AROUND BASIN

F/L 24" CMP = 938.40

CP #6
1/2" IRON BAR
CONTROL POINT
N: 1307990.05
E: 2710673.62
ELEV. = 969.13

+/-180 LF. 18" SOLID, HDPE N-12 PIPE. ANCHOR AT BOTTOM OF SLOPE AND INSTALL CMP FLARED END SECTION WITH 4' WIDE x 15' RIP RAP. UPPER END TO HAVE 30" RD. NYLOPLAST INLET WITH CAST IRON DOMED LID. PLACE 2' x 6" THICK, WIDE CONCRETE COLLAR AROUND BASIN

+/-180 LF. 21" SOLID, HDPE N-12 PIPE. ANCHOR AT BOTTOM OF SLOPE AND INSTALL CMP FLARED END SECTION WITH 4' WIDE x 15' RIP RAP. UPPER END TO HAVE 30" RD. NYLOPLAST INLET WITH CAST IRON DOMED LID. PLACE 2' x 6" THICK, WIDE CONCRETE COLLAR AROUND BASIN

POTENTIAL BORROW AREA

